

Chainslings Grade 8

Grade 8 chainslings can be assembled to your own requirements. We can supply chainslings ranging from 1.5 tonne to 67 tonne. Assembly can be single leg, 2 leg, 3 leg & 4 leg.
(please see chart below to determine your requirements).

Fitting Options



1 Leg



Eye type
Grab Hook



Component
Connector



Master
Ring



Quad Master
Ring



Clevis type
Reeveable
Egg Link



Clevis Latch
Hook



Safety hook
Clevis Type



'C' Hook
Clevis Type



2 Leg (brothers)

- ◆ Assembled to your exact requirements
- ◆ Swivel Hooks also available



4 leg

Chain Diameter	α angle from leg to vertical		α angle from leg to vertical		α angle from leg to vertical		α angle from leg to vertical		Sling Configuration
	90°	0-45°	45-60°	0-45°	45-60°	0-45°	45-60°		
Factor	1	1.4	1	2.1	1.5	2.1	1.5	Working Load Limit In Tonnes	
7mm	1.50	2.12	1.50	3.15	2.24	3.15	2.24		
8mm	2.00	2.80	2.00	4.25	3.00	4.25	3.00		
10mm	3.15	4.25	3.15	6.70	4.75	6.70	4.75		
13mm	5.30	7.50	5.30	11.20	8.00	11.20	8.00		
16mm	8.00	11.20	8.00	17.00	11.80	17.00	11.80		
20mm	12.50	17.50	12.50	26.50	19.00	26.50	19.00		
22mm	15.00	21.20	15.00	31.50	22.40	31.50	22.40		
26mm	21.20	30.00	21.20	45.00	31.50	45.00	31.50		
32mm	31.50	45.00	31.50	67.00	47.50	67.00	47.50		