


Code	Thread [mm]	Load capacity [kg]	a [mm]	b [mm]	c [mm]	d [mm]	e [mm]	n [mm]	n max [mm]	 [mm]	Weight [kg/pc.]
PLDW 0,3 t	M8	300	30	38	54	13	38	20	100	34	0.45
PLDW 0,5 t	M10	500	30	38	54	13	38	20	180	34	0.45
PLDW 0,7 t	M12	700	35	48	54	13	38	22	200	34	0.48
PLDW 1 t	M14	1,000	35	48	54	13	38	22	200	34	0.49
PLDW 1,5 t	M16	1,500	35	48	54	13	38	33	250	34	0.51
PLDW 2,5 t	M20	2,500	35	55	75	16	55	33	250	46	1.10
PLDW 4 t	M24	4,000	40	66	82	17	63	40	300	50	1.50
PLDW 6,7 t	M30	6,700	50	70	92	23	72	40	300	60	2.80
PLDW 8 t	M36	8,000	50	91	120	23	92	55	300	75	4.30
PLDW 10 t	M42	10,000	65	91	120	27	92	60	300	75	5.10
PLDW 12 t	M45	12,000	65	91	120	27	92	68	-	75	5.20
PLDW 12,5 t	M48	12,500	65	116	120	27	92	68	300	75	5.40
PLDW 24 t	M56	24,000	70	105	154	33	110	84	300	95	10.20
PLDW 25 t	M64	25,000	70	105	154	33	110	96	300	95	11.00
PLDW 40 t	M72	40,000	90	130	213	45	170	110	500	145	29.00
PLDW 45 t	M80	45,000	90	130	213	45	170	120	500	145	30.00
PLDW M90 - 55 t	M90	55,000	90	130	213	45	170	135	500	145	32.00
PLDW M100 - 55 t	M100	55,000	90	130	213	45	170	150	500	145	35.00

Code	Thread [inch]	Load capacity [lbs]	a [inch]	b [inch]	c [inch]	d [inch]	e [inch]	n [inch]	n max [inch]	 [inch]	Weight [lbs/pcs.]
PLDW U 3/8	3/8"-16	1,100	1.18	1.50	2.13	0.51	1.50	0.59	-	1.34	1.00
PLDW U 1/2	1/2"-13	1,500	1.38	1.89	2.13	0.51	1.50	0.79	-	1.34	1.06
PLDW U 5/8	5/8"-11	3,300	1.38	1.89	2.13	0.51	1.50	0.98	-	1.34	1.10
PLDW U 3/4	3/4"-10	4,400	1.38	2.17	2.95	0.63	2.17	1.18	-	1.81	2.43
PLDW U 1	1"-8	8,800	1.57	2.60	3.23	0.67	2.48	1.57	-	1.97	3.30
PLDW U 1 1/4	1 1/4"-7	14,700	1.97	2.76	3.62	0.91	2.83	1.77	-	2.36	5.70
PLDW U 1 1/2	1 1/2"-6	17,600	1.97	3.58	4.72	0.91	3.62	2.17	-	2.95	9.50
PLDW U 1 3/4	1 3/4"-5	22,000	2.56	3.58	4.72	1.06	3.62	2.36	-	2.95	11.20
PLDW U 2	2"-4.5	27,500	2.56	4.57	4.72	1.06	3.62	2.60	-	2.95	11.90
PLDW U 2 1/2	2 1/2"-4	39,600	2.76	4.13	6.06	1.30	4.33	3.78	-	3.74	22.40

Safety factor 4

Important: Subject to technical changes!