



Code	Thread [mm]	Load capacity [kg]	a [mm]	b [mm]	c [mm]	d [mm]	e [mm]	f [mm]	n [mm]	n max [mm]	[mm]	Weight [kg/pc.]
PLGW 0,3 t	M8	300	25	45	10	27	53	35	15	90	6	0.20
PLGW 0,5 t	M10	500	25	45	10	27	53	35	15	160	6	0.21
PLGW 0,7 t	M12	700	30	55	12	32	63	43	20	160	8	0.32
PLGW 1,5 t	M16	1,500	35	64	14	36	70	50	25	160	10	0.48
PLGW 2,3 t	M20	2,300	40	73	16	41	81	54	30	160	12	0.58
PLGW 3,2 t	M24	3,200	50	86	18	50	93	69	35	-	14	1.10
PLGW 4,9 t	M30	4,900	60	110	25	60	114	90	45	-	17	2.20
PLGW 7 t	M36	7,000	70	132	31	70	136	108	55	-	19	3.80
PLGW 9 t	M42	9,000	80	152	36	72	153	126	65	-	22	5.70
PLGW 12 t	M48	12,000	95	179	42	88	179	148	75	-	24	8.90

Code	Thread [inch]	Load capacity [lbs]	a [inch]	b [inch]	c [inch]	d [inch]	e [inch]	f [inch]	n [inch]	n max [inch]	[inch]	Weight [lbs/pc.]
PLGW U 3/8	3/8"-16	1,100	0.98	1.77	0.39	1.06	2.09	1.38	0.59	-	1/4"	0.44
PLGW U 1/2	1/2"-13	1,500	1.18	2.17	0.47	1.26	2.48	1.69	0.79	-	5/16"	0.71
PLGW U 5/8	5/8"-11	3,300	1.38	2.52	0.55	1.42	2.76	1.97	0.98	-	3/8"	0.99
PLGW U 3/4	3/4"-10	4,400	1.57	2.87	0.63	1.61	3.19	2.13	1.18	-	1/2"	1.28
PLGW U 1	1"-8	6,600	1.97	3.39	0.71	1.97	3.66	2.72	1.38	-	9/16"	2.43
PLGW U 1 1/4	1 1/4"-7	8,800	2.36	4.33	0.98	2.36	4.49	3.54	1.77	-	5/8"	4.63
PLGW U 1 1/2	1 1/2"-6	15,400	2.76	5.20	1.22	2.76	5.35	4.25	2.17	-	7/8"	8.38
PLGW U 1 3/4	1 3/4"-5	19,800	3.15	5.96	1.42	2.83	6.02	4.96	2.56	-	1"	12.57

Safety factor 4

Important: Subject to technical changes!