

## FELCO C9 WIRE ROPE CUTTER

- **Reliable:** unbreakable hardened handles made of forged aluminium with a lifetime guarantee/blades and fastenings in high-quality hardened steel/parts subject to wear and tear can be replaced
- **Efficient:** clean, precise cut without crushing the cable thanks to the triangular cutting system/easy and durable cutting adjustment
- **Ergonomic:** lightweight handles/helpful lever effect/comfortable plastic coating

The C9 cutter is Felco's smallest two-handed wire cutter. It features Felco's patented "triangular cut", a system designed to cut rope smoothly - without being crushed. The C9 has hardened steel blades and center bolt and unbreakable forged aluminum alloy handles with plastic covering for good grip. The tool cuts wire rope up to 3/8 inch or 9 mm thick, high tensile steel strands up to 7 mm thick, stainless steel strands up to 6 mm, extra tough wire rope or strands up to 5 mm. In addition, it cuts electric cables of copper, aluminum or steel-cored aluminum, and aluminum or copper rods up to 9 mm. The C9 also cuts steel rods up to 7 mm and tempered steel spring wire up to 4 mm in diameter.

Length 330 mm. Weight ca 794 gram.



### CUTTING CAPACITIES

MATERIAL	MAXIMUM CUTTING DIAMETER
Galvanized steel wire rope, fibre core	9mm (0.35in)
Galvanized steel wire rope, steel core	8mm (0.31in)
Hard steel wire rope, resistance 160 kg/mm <sup>2</sup>	7mm (0.28in)
Non-oxidable steel wire rope, resistance 190 kg/mm <sup>2</sup>	6mm (0.24in)
Extra tough wire rope and strands, resistance 210 kg/mm <sup>2</sup>	5mm (0.2in)
Electric cables (copper or aluminium) with steel core)	9mm (0.35in)
Aluminum- or copper rods	9mm (0.35in)
Iron rods, resistance 60 kg/mm <sup>2</sup>	7mm (0.28in)
Tempered spring wire	3mm (0.12in)
Welded wire mesh	X
Rubber conveyor belt	X